
Subject: Re: MacIntosh XRT 29 Comments
Posted by [Jim Griffin](#) on Sun, 03 Apr 2005 23:06:24 GMT
[View Forum Message](#) <> [Reply to Message](#)

Well, if you read what I said about the Mac design you should realize that 3000 Hz is too high to cross with this design unless you use smaller than 4" diameter drivers spaced really close together. You need to be shooting for a crossover in the low 2000's Hz(possible) or sub 2000 which the PT2 can not do. I have used the PT2 type planar as low as 2300 Hz (third order). Unless you have skill in metal work or access to such technology, I would be thinking of what you can do with wood working skills. You can build a rectangular box similar to the outside dimensions of the Mac box and brace it to strengthen the baffle. I have used multiple full shelf internal braces in similar wide face boxes. I don't understand what wings would for you unless you are thinking of an open baffle application. If you go open baffle, you need to equalize a lot to cover the lower freq ranges plus add stereo woofers to cover the bass area. The NSBs are too small and inefficient (bass wise) to do much for you down low without a lot of dipole EQ. Maybe 34 NSBs per side will help but EQ will be needed to make the open baffle work. By the way, you mentioned rounding the baffle edge for BSC. Rounding of the front baffle does nothing for BSC but does help baffle edge dispersion higher in frequency. With your active crossover the BSC you will have to be EQed (that is if you are using a vented or closed box). Of course no BSC for open baffle but dipole compensation will have to be done for good results.
