
Subject: Re: Need a bit of help with cab volume
Posted by [djn](#) on Tue, 08 Aug 2006 17:29:35 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Jim, here are the drivers I have. I have sixteen of both. The drivers I have are: the Onkyo tweeter from PE: 3/8" Mylar tweeter with neodymium magnet mounted on a pole piece. Originally designed to be mounted on the pole piece of a driver to create a coaxial speaker. Tweeter can be removed from pole mount, but only with great difficulty. Limited quantities. Specifications: *Power Handling: 20 watts RMS/40 watts max *VC dia: 3/8" *Znom: 6 ohms Re: 4.00 ohms *Frequency range: 6,000-20,000 Hz *Fs: 4,200 Hz *SPL: 87 dB 2.83V/1m *Tweeter Dimensions: Overall Diameter: 1-3/8", Cutout Diameter: 1", Mounting Depth: 1/2". And the Pioneer mid from PE: This lovely 4" driver is an all-around great performer that offers excellent full-range performance in a small, fully-shielded package. These drivers are great for many different types of designs, from dipole surround speakers to center channels, and are even perfect for line arrays! Driver features: 3/4" V.C. on paper former, large flat spider, paper cone, rubber surround, and a paper dustcap. Specifications: *Power Handling: 5 watts RMS/10 watts max *VC dia: 3/4" *Le: .60 mH *Znom: 8 ohms *Re: 7.50 ohms *Frequency range: 75-15,000 Hz *Fs: 105 Hz *SPL: 86 dB 2.83V/1m *Vas: .08 cu. ft. *Qms: 5.0 *Qes: .90 *Qts: .76 *Xmax: 1 mm *Driver Dimensions: Overall Diameter: 4", Cutout Diameter: 3-11/16", Mounting Depth: 2-1/4".
