
Subject: Re: anyone tried equidistant spacing?

Posted by [Marlboro](#) on Sun, 04 Mar 2007 12:08:13 GMT

[View Forum Message](#) <> [Reply to Message](#)

My thought is to space the tweeters equidistantly - probably packed tightly together at the middle and expand to maybe 3" apart at the ends of the line. That way I would get earlier nodes but it should blur the frequency where I get nodes making them (hopefully) less noticable. Q1. Has anyone tried this before? Any thoughts whether theoretical or practical? -----I SHOULD THINK THIS WOULD MAKE THE COMBING WORSE. My second option is to scrap the tweeter array and go for a needle design with one tweeter at ear height. (The differing -3dB VRS -6dB distance response won't be a problem as I will only ever use them at one fixed distance.) THIS IS YOUR BETTER CHOICE IN MY OPINION. GET A COUPLE OF REALLY HIGH QUALITY TWEETERS. ITS A SHAME THAT THE SHIPPING WOULD BE SO HIGH FOR 60 DAYTON NEO'S, BUT YOU MIGHT WANT TO ASK THEM. THEY WEIGH HARDLY ANYTHING. ALSO THEY ARE MADE IN CHINA, MAYBE DAYTON WOULD SHIP SOME DIRECTLY TO YOU FROM CHINA THIS WOULD ALLOW YOU TO HAVE A REAL ARRAY WITH THE TWEETER PORTION AND DEPENDING ON HOW TIGHTLY YOU CUT THE FLANCES YOU COULD PUSH COMB FILTER DISTORTION OUT TO BEYOND AUDIBILITY. Q2. At what frequency do the significant spacial clues stop? Will the single tweeter be noticable if I cross over quite high - say over 3KHz? YOUR CROSSOVER FOR THE TWEETER WILL DEPEND ON YOUR DISTANCE APART FOR THE MIDRANGES. SINCE YOU ARE USING 5 INCHERS, YOU CAN PROBABLY GET THE C-TO-C SPACING AT 5.25 OR LESS. $13560/5.25 = 2582$. SO YOU WOULDN'T WANT TO CROSS ANY HIGHER THAN 2600 HZ. REMEMBER TO GET THE TWEETERS CLOSE TO THE MIDS ALSO SO YOU DON'T HAVE HORIZONTAL COMBING TOO. Finally I have also thought of a curved array to eliminate any phase differences. I would just use a baffle with a concave curvature of 3m radius. However I am a bit concerned about focusing the drivers all down to one point and the affect this may have on frequency response as the directivity of the drivers narrows at higher frequencies. (Applies to both woofer and tweeters here) CAN'T HELP HERE, THOUGH LOTS OF PEOPLE DO THAT. HOPE THIS WAS A LITTLE BIT HELPFUL. MAYBE JIM GRIFFIN WILL JUMP IN AND GIVE THE BOTTOM LINES. Email me if you want to contact him directly and I'll give you his email address, or you can search this forum for it, and contact him directly. Jim was very helpful to me when I first started building my array. Marlboro
