

---

Subject: 4Pi WIDTH, ROOM BOOST AND PORT PLACEMENT?

Posted by [mhammill](#) on Sat, 18 May 2002 22:34:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Greetings, As soon as my parts arrive I'll be starting a pair of 4Pi theaters I'm really pumped to get started. I will be using the full 48" of the birch ply for the vertical height and mount the horn at ear level centered at about 38" and the woofer close below while retaining the same internal volume as called for by the plans. I will use 4" port tuned to 26hz. The room is small and WAF must be factors. QUESTIONS 1. Is 22.75" wide enough for the front baffle for (is it wave launch) or will this and having the woofer mounted higher (further from the floor have any affect on the bass response? 2. Since I have a archway opening into the dining room area behind my speaker placement spot a straight rear port is not an option, but would having the port fire at floor level and to the side or corner give additional room boost by using the side wall and partial rear corner as a reflective surface? Would this have any advantage or disadvantage over a floor level outside corner front port? 3. Has anyone ever tried a Karlson slot for the bass in a similar design? How might this be accomplished? 4. I have seen the Karlson websight but have not fully absorbed the design theory. Could the tapered port create a variable tuning point in a TQWP? I love the multiple approach attack. Thanks Mike H.