
Subject: Re: Power Handling of individual components
Posted by [Wayne Parham](#) on Thu, 22 May 2003 18:20:07 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi Adrian! You wrote: >> I notice what you've done is used a swept sine wave of 50VRMS >> (~312Wrms) to take the measurements (312W is HUGE for >> midrange/tweeter... am wondering why you've used such a high value?). The crossovers are used with speaker motors that handle up to 1000 watts. So this voltage was chosen because it represents a level that is commonly presented to these crossovers. It shows the power curve for each part too, which is what I most wanted to show. It is interesting that power handling requirements aren't specific values, but rather are a function of frequency and are different for each part. >> Anyway, my question is, how do I do the sine wave sweep in SPICE >> so I can analyse the voltage going across particular components? When you do AC analysis, it asks a range of frequencies to choose. Your earlier model of the crossover used this same sort of thing to make the response graph. >> Also, how do you select which component (EG: C4, R2, etc) that you >> wish to analyze? (in the diagrams, v6 is used for a number of >> components). Instead of plotting V1 and V6 (the woofer and tweeter) you may choose to plot the voltage across any other part. In the example given in the speaker crossover document, it requires 100W or so resistors... a very high value. It does say though that resistors 25 or 50% of the wattage can be used for the tweeter part (not woofer though? :(not much point using smaller ones for the tweeter then if that's so, because you'd need to get 100W ones for the rest of the circuit anyway). Parts Express has resistors with maximum power of 20W, but don't come in many values. They are wirewound type, this is OK? I'd suggest you use non-inductive resistors. Parts Express has 10 watt, 100 watt and 200 watt non-inductive

Wouldn't this be different for different circuits? The formula describes the relationship between inductance, frequency and impedance. So if you know the inductance of a coil and the frequency you will present to it, the formula will tell you its impedance. You can also rearrange the formula to find any other term you wish. >> For the other 8db attenuation for the midrange (4ohm resistor in >> series then parallel with midrange), how can I determine what >> components for maximum power handling I would need. Do I need to >> make a SPICE model of them? You could. You could also calculate it by hand - There are formulas for power distribution in the "Pi Alignment Theory" document. These are standard formulas, so you can also find them in any electronics textbook. Wayne