
Subject: Re: Crossover Document

Posted by [Adrian Mack](#) on Mon, 12 Jan 2004 05:59:20 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hey Wayne I had a feeling the lower and upper bounds were the points where both drivers are still generating output audibly, but at an attenuated level, sort of before it starts going "offline". Or something like that, I was just wondering if you had a way to calculate these limits or whether you just choose a point, like at -6db attenuation, -12db, etc. Since the crossover is a reactive component, then phase shift from this would be considered. On the 3rd order network, you've just told me that it's 135deg at the crossover frequency (which would be the border before it starts becoming destructive). For this example I'll have 1.6KHz as the crossover frequency. If we shift the tweeter forward 1.05", which is 45deg or $1/8\lambda$ of 1.6KHz, then add that 45deg to the 135deg of phase shift produced by a 3rd order crossover at the crossover point, would make the sound sources 180deg apart and complete cancellation would occur at the crossover frequency, is this correct? Can we consider the acoustic centers as well. Put the listener on axis in front of the speaker, but have the acoustic center of the tweeter 1.05" in front of the woofer's acoustic center. Assume same conditions as above example - 1.6KHz crossover point and 3rd order crossover on both woofer and tweeter. Even on-axis then you would have a huge cancellation at the crossover frequency if we shift the acoustic center of the tweeter 1.05" forward. But isn't the on-axis and null-axis positions shifted if the acoustic centers aren't aligned? Or is it only the null-axis that is shifted? That cancellation on-axis I described above would still occur though and on-axis, even if the axis is shifted? Thanks! Adrian
