
Subject: Re: 8 Pi Tuning

Posted by [Jeff Aiken](#) on Fri, 24 Sep 2004 04:37:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Wayne, thanks for the reply. I did make a mistake in that I calculated the driver volume to be .75ft³ instead of 75in³. So, here's the internal volume I calculate, now (sorry so lengthy, my geometry is a little rusty ;). Using the 8 Pi external dimensions I've subtracted 1.5" from each dimension (2*.75" material) to arrive at the internals. 1) I calculated the front "cube" portion of the cabinet first: 24.5"W x 30.5"H x 9.6"D = 7173.6in³ or 4.15ft³ 2) I calculated the rear "trapezoid" portion as $(A=h/2(b_1+b_2)) \times \text{Height}$: $(5.25/2(12.5+24.5))\text{in}^2 \times 30.5\text{H} = 2962.3125\text{in}^3$ or 1.714ft³ 3) Add front and rear portions and get 5.864ft³ total internal before subtracting mid-horn or bracing. 4) I estimated the mid-horn flare w/mounting plate to be about 1.12ft³ and the driver to be .043ft³ totaling 1.163ft³. 5) Subtract 1.163 from 5.864 and total volume remaining is 4.701ft³. 6) I only subtract 5% for bracing giving 4.466ft³ total internal volume. According to WinISD, using 3 ports (1.625x3.5 as the plans suggest) this tunes a 4.466ft³ cabinet to 62hz with a F3 = 50hz and a 5.4dB peak at 70hz with the Alpha 10. To get a flat response to 40hz WinISD says the ports would each have to be 4.43" long. Am I still calculating something wrong? Is WinISD's vent calculation inaccurate (seems I read that somewhere)? Wayne, if you're bored (you have to be if you've read this far ;p) and enjoy toying with the mathematically challenged I still appreciate your help and now your patience. ;^> Sorry, if I'm beginning to aggravate. Just trying to grasp things before I make the plunge. Thanks, Jeff
