Subject: Weak Joint

Posted by Champion on Thu, 06 Mar 2008 21:29:05 GMT

View Forum Message <> Reply to Message

I am half way through building a 3pi cabinet. But one of the joint has very small gap (I think the MDF is bent slightly and I did not have enough clamp). I am not sure if the joint is strong enough so what should I do? Thanks.

Subject: PL Adhesive

Posted by Wayne Parham on Thu, 06 Mar 2008 21:43:17 GMT

View Forum Message <> Reply to Message

MDF is pretty inexpensive so if it isn't veneered, you could just start over. On the other hand, you could repair the cabinet by filling the joint with PL adhesive. Force the adhesive in the crack to fill it completely. It will expand slightly as it dries. Then sand it smooth and finish the cabinet with veneer or paint as you originally intended. This adhesive is very strong even when there is a gap between surfaces up to 3/8". I'm sure it will solve your problem.

Subject: Re: PL Adhesive

Posted by Champion on Thu, 06 Mar 2008 23:21:59 GMT

View Forum Message <> Reply to Message

Thanks for your suggestion Wayne. That is very useful to know. I think I will keep going and if the joint is bad then I will repair it. The gap is pretty small (less than 0.5mm) and I am not sure if the gap is along the whole width of the seam or just the outter edge. But I know that wood is not in good contact as the adhesive has not squeezed out like they other joints when I clamp them together. BTW, can PVA glue (titebond II) bridge any gap at all? Or the joint will fail if the wood are not in good contact? Thanks.

Subject: Re: PL Adhesive

Posted by Wayne Parham on Fri, 07 Mar 2008 17:26:32 GMT

View Forum Message <> Reply to Message

I'd use PL adhesive to fill a gap. White glue isn't really good for that.