

---

Subject: 2-Pi towers port freq???

Posted by [Wayne-o](#) on Tue, 28 Oct 2008 01:07:50 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

What is the port freq. of the 2-pi tower? It looks like 50 hz. Thanks

---

---

Subject: 40Hz

Posted by [Wayne Parham](#) on Tue, 28 Oct 2008 02:58:28 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

---

Subject: Re: 40Hz

Posted by [Wayne-o](#) on Tue, 28 Oct 2008 04:43:39 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

OK , I guess the program i am using does not take into account for the resonant effect of the tower.

---

---

Subject: Re: 40Hz

Posted by [Wayne Parham](#) on Tue, 28 Oct 2008 17:00:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

No, it's not that. The driver and port are placed where internal standing wave nodes don't affect response. The Helmholtz resonance would be about 45Hz even without insulation. After insulation is applied, it drops to 40Hz. The insulation is to damp standing waves, mostly to trap midrange energy. But it also tends to lower the Helmholtz resonance as a size effect. Anyway, long story short, cabinet tuning is 40Hz.

---

---

Subject: Re: 40Hz

Posted by [Wayne-o](#) on Tue, 28 Oct 2008 23:35:54 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Thanks!!!

---