

---

Subject: Alternate woofer for 3Pi  
Posted by [Stollie](#) on Wed, 21 Jan 2009 22:09:08 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Has anyone used an alternate woofer for the 3Pi? Perhaps the 4012HO Definimax?

---

---

Subject: Re: Alternate woofer for 3Pi  
Posted by [Wayne Parham](#) on Wed, 21 Jan 2009 23:59:11 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

the upper midrange. That's really critical in a speaker like this, you need one that is designed for use at relatively high frequency and has a well damped cone. The Magnums, with their mesh dust caps, tended to do fine up to a point, and then breakup was sharp.

---

---

Subject: Re: Alternate woofer for 3Pi  
Posted by [Stollie](#) on Thu, 22 Jan 2009 00:21:27 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Thanks Wayne. I'm just partial to cast frames vs stamped steel. What about the Delta Pro-12A 12" Cast Frame Driver. Says' it good past 4K. It may be a bit bass shy, but that could be handled via multiple subs.

---

---

Posted by [Wayne Parham](#) on Thu, 22 Jan 2009 04:50:25 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

subs. Makes the bass smoooooth. Multi-sub configuration

---

---

Posted by [Stollie](#) on Thu, 22 Jan 2009 06:17:43 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Thanks Wayne, I've looked at the 4Pi, but I'm not keen on the idea of the woofer practically sitting on the floor. There's also the cost consideration of the JBL2226. But I'll look again. Would you kindly send plans for both the 3 and 4 Pi?

---

---

Posted by [Wayne Parham](#) on Thu, 22 Jan 2009 17:32:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I rest mine on small angled risers, which lift the front of the speakers about three inches and the rear only about one inch. This has an effect of angling the forward axis up slightly. In this position, the tweeter is at ear level when seated. Another option that is made attractive when using multiple subs is to put the speakers on stands, a foot or foot and a half tall. This puts the midwoofer at ear level seated. The floor bounce that would be created by raising the midwoofer is mitigated by use of multiple subs. For this to work, a sub has to be put a few feet away from each speaker and in a different position in all three planes. The floor bounce notch is found in the upper midbass to lower midrange, so the subs have to be low-passed relatively high, 90Hz to 120Hz or so is fine. It will blend perfectly. If further modal smoothing is desired at lower frequencies, another sub or two can be placed further away, and crossed over lower. I suggest trying both approaches. You can use books or milk cartons as temporary stands to try various placements in your room. When you find what works best, make attractive stands to accomplish that permanently. Positioning and subs

---

---

Posted by [Stollie](#) on Thu, 22 Jan 2009 18:25:28 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Thanks again. Can I have plans for both the 3Pi and 4Pi?.

---

---

Subject: You've got mail!

Posted by [Wayne Parham](#) on Fri, 23 Jan 2009 02:05:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

---