

---

Subject: 2-pi tower.

Posted by [Wayne-o](#) on Sat, 08 Aug 2009 05:44:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Does the tower pipe rez. increase the spl in the 75-80 hz range ?

I know you have said that you are using the port hemoholtz as the primary ,but the pipe freq. is still there. Thanks, I hope you can put these words together right. I dont have any software that models these type of cabinets.

---

---

Subject: Re: 2-pi tower.

Posted by [Wayne Parham](#) on Sat, 08 Aug 2009 12:41:53 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

help develop this speaker, since the tower is physically tall and would suffer pipe modes in the passband. The woofer and port positions were chosen so Helmholtz resonance is the predominate tuning mechanism, reducing the influence of pipe modes by both position and damping.

You'll notice the plans suggest insulation span the cross-section of the cabinet, laying on the braces spaced 1/3rd the way from the top and 1/3rd the way from the bottom. This, in addition to the insulation on the cabinet walls and the position of the port and woofer, smooths pipe modes to the point where they are invisible to measurement and inaudible to the ear.

---

---

Subject: Re: 2-pi tower.

Posted by [Wayne-o](#) on Sun, 09 Aug 2009 02:51:23 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Thanks again.

---