Subject: towers

Posted by Dpend on Thu, 07 Jul 2011 15:29:55 GMT

View Forum Message <> Reply to Message

should the fronts of the cabinet be between the sides or on the face so the sides are hidden. Or does it not make any difference

Subject: Re: towers

Posted by Bill Epstein on Thu, 07 Jul 2011 19:31:03 GMT

View Forum Message <> Reply to Message

I always put the face and rear over the sides, with the tops and bottom inside all four. I think it's structureally stronger, easier to glue-up without fasteners, and especially, the top and bottom pieces help square the glue-up. On top of that, if you cut 3 extra top and bottom pieces per cabinet, you have ready made, exact size braces.

File Attachments

1) UniversityAltec build 005.jpg, downloaded 2039 times

Subject: Re: towers

Posted by Dpend on Fri, 08 Jul 2011 00:29:24 GMT

View Forum Message <> Reply to Message

Thats an excellent idea the braces would be the same size. thanks for replying. I just came home with the would today. I found some 5/8 shelving panels already veneered for less than 14.00 and there 96 inch long.

Subject: Re: towers

Posted by breakfastchef on Fri, 08 Jul 2011 02:51:43 GMT

View Forum Message <> Reply to Message

I agree with Bill Epstein; the front should over the sides. For super easy glue-up of the front and rear panels, I used biscuits. Everything lined up quickly providing me ample time to install clamps and wipe glue drips.

File Attachments

1) m_20081224_0004.JPG, downloaded 1889 times

Subject: Re: towers

Posted by Dpend on Fri, 08 Jul 2011 03:46:24 GMT

View Forum Message <> Reply to Message

Thanks guy's I love seeing the pics, really helps out. They go straight to my thumb drive

Subject: Re: towers

Posted by Dpend on Fri, 08 Jul 2011 03:48:31 GMT

View Forum Message <> Reply to Message

By the way how do they sound?