
Subject: Home Built Table Extrodinaire

Posted by [Manualblock](#) on Wed, 09 Aug 2006 21:47:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

This guy has designed a home-made table that uses the intake valve from a Harley Davidson Shovlehead engine the matching valve guide and a titanium ball bearing as a main bearing. Wait; it gets better. But let me provide the link.

<http://www.altmann.haan.de/turntable>

Subject: That's pretty cool!

Posted by [Wayne Parham](#) on Thu, 10 Aug 2006 14:02:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

I like it a lot. The first couple of pictures look interesting but kind of hackish. But then as I went through what he did, I realized he thought it through and it is actually very precise. Cool!

Subject: Re: That's pretty cool!

Posted by [Manualblock](#) on Thu, 10 Aug 2006 14:15:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

Yes; it isn't art; but he makes it clear he is experimenting as he goes along. There is some controversey regarding the Valve guides. Evidently they are designed to expand with heat and form a tight seal; something that won't happen on a turntable. I say VPI sells their bearing for a very fair price; use that.

Subject: Re: That's pretty cool!

Posted by [Wayne Parham](#) on Thu, 10 Aug 2006 15:50:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

The clearance between a new Harley valve and valve guide is about 0.0015". Older Harleys required more clearance but they were still pretty tight. The clearance is there to allow for oil film and not for expansion. Metals do expand from heat, so there is a tiny expansion, but the main reason for the clearance is that there be room for oil film.

Valve guides are designed to dissipate the heat from valve friction into the head. The best head designs have a large surface area contact between the valve guide and head so that heat transfer is good. Old Harleys are an example of a bad design, there wasn't enough surface area so their valve guides got too hot. New ones like used in the Evolution are better; They figured it out. The

thing is, you can't make a valve guide larger hoping to account for heat expansion. If the valve chatters inside the guide, it will make it hotter than if the fit were closer. Ideally, you want the valve to ride on a film of oil and have basically zero clearance beyond what it takes to provide for the oil. So if you have a valve guide that gets hot enough to expand appreciably, then it has too much clearance and will get hot from chattering. Long story short - A new valve fits nicely into a new valve guide with very little clearance. After you apply a thin film of oil, there is zero clearance.

Subject: Re: That's pretty cool!
Posted by [Manualblock](#) on Thu, 10 Aug 2006 22:46:35 GMT
[View Forum Message](#) <> [Reply to Message](#)

Well; that clears that discussion up. Looks like a go ahead on the table experiment.
