

---

Subject: RE: mounting woofer

Posted by [Bill Epstein](#) on Sun, 20 Nov 2005 20:38:48 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Late to the thread below but visiting with Steve and seeing GarMans incredible Winbraces I thought I'd show what I think is a simple and easy way to double the front baffle and "embrace" the woofer: I cut the inner baffle piece a little over-size to flush-trim with the router after glue-up in case of slippage. Clamping the 2 together I drill the pilot hole for the Jasper pin through both. Then rout the appropriate size hole in inner and outer. For glue-up I place the woofer in the inner baffle to correctly locate the outer baffle. I protect the edges from glue with wax paper. Smear up with PVA glue and drive home a buncha' screws I'll remove later. Next day flush trim the edges of the inner to match the outer baffle. Now I'm thinking about sizing the inner baffle to make a rabbet so it slips inside the box. Maybe. I do the same to mount the ports so the black schedule 40 pipe doesn't show. Now I've seen how nice the plastic flared ports look I'm re-thinking that.

---

Subject: Re: RE: mounting woofer

Posted by [Wayne Parham](#) on Mon, 21 Nov 2005 15:11:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

That's a great photo, illustrates a window brace perfectly. Thanks!

---