Subject: RE: mounting woofer
Posted by Bill Epstein on Sun, 20 Nov 2005 20:38:48 GMT
View Forum Message <> Reply to Message

Late to the thead below but visiting with Steve and seeing GarMans incredible Winbraces I thought I'd show what I think is a simple and easy way to double the front baffle and "embrace" the woofer:I cut the inner baffle piece a little over-size to flush-trim with the router after glue-up in case of slippage.Clamping the 2 together I drill the pilot hole for the Jasper pin through both. Then rout the appropriate size hole in inner and outer.For glue-up I place the woofer in the inner baffle to correctly locate the outer baffle. I protect the edges from glue with wax paper. Smear up with PVA glue and drive home a buncha' screws I'll remove later.Next day flush trim the edges of the inner to match the outer baffle.Now I'm thinking about sizing the inner baffle to make a rabbet so it slips inside the box. Maybe.I do the same to mount the ports so the black schedule 40 pipe doesn't show. Now I've seen how nice the plastic flared ports look I'm re-thinking that.

Subject: Re: RE: mounting woofer
Posted by Wayne Parham on Mon, 21 Nov 2005 15:11:44 GMT
View Forum Message <> Reply to Message

That's a great photo, illustrates a window brace perfectly. Thanks!