

---

Subject: Time Alignment - Horn/Compression & Woofer

Posted by [jshoc](#) on Mon, 13 Feb 2006 01:20:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Is time aligning a compression driver with horn flare and a woofer important? For example, if the diaphragm of a compression driver was aligned with a voicecoil of the woofer, the horn flare in my case, JBL 2385a, would be projecting out about 6" from the woofer. What am I missing? Jim

---

---

Subject: Re: Time Alignment - Horn/Compression & Woofer

Posted by [Wayne Parham](#) on Mon, 13 Feb 2006 17:05:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

If interaction of sound sources causes frequency anomalies - cancellation at certain frequencies - then you'll notice an unusual sound. It won't sound natural. But this is really a manifestation of conditions that cause nulls, not so much due to small delays themselves. Time shifts of less than

conditions of our environment that make these cues less important. When you hear a time alignment problem, it is purely a manifestation in the frequency domain that you hear, not the actual misalignment. Until the sound sources are so far apart as to cause an audible echo, delay is impossible to hear, except due to the frequency notches that may result. To physically align sound sources is pretty easy. But you're right that a horn tweeter is longer than a direct radiating midwoofer, so physical alignment might be sort of awkward. Also consider that there are many things that introduce time jitter with respect to frequency, so you would never be able to obtain perfect time alignment anyway. Both the woofer and the tweeter are reactive, so that means their phase moves with respect to frequency. This makes them each act as though they were moving in physical space. The woofer has a resonance down low which will move its apparent position by as much as several feet. Then, through the crossover region, there is a phase shift too. The horn introduces several phase peaks near its flare frequency, and only at higher frequency does phase become relatively constant. As you can see, phase jumps all around through the audio band, so perfect time alignment is not possible. What is possible, and I think most important, is to limit

don't want destructive interference between two overlapping sound sources because they'll cause a frequency null. And since position and path length enter into the picture, interaction between sound sources is different throughout the room. The goal of a designer is to limit interactions in the target listening area to those which will not cause destructive interference, and that means

---

---

Subject: Re: Time Alignment - Horn/Compression & Woofer

Posted by [Earl Geddes](#) on Fri, 17 Feb 2006 20:50:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

It is pretty important to get the crossover right. And don't forget that the LP filter for the woofer has a delay so that puts the woofer back a few inches. In my speakers the woofer and compression driver have just about the exact same delay to the far field even though the compression driver is several inches further back than the woofer.

---