

---

Subject: Basic requirements for phase plug in horn loaded cone driver?

Posted by [Norris Wilson](#) on Fri, 28 Nov 2008 21:58:24 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Could someone knowledgeable explain what the basic requirements would be for a phase plug of a woofer for horn loading? What would be the advantage of using a woofer with a phase plug versus one without? There are a few midrange and mid-woofers available with phase plugs that look like they could be possible candidates for a horn loaded design. But, I am not sure what to look for in their specifications that indicates a good woofer for horn loading? Thanks to those who can enlighten me. NW

---

---

Subject: Re: Basic requirements for phase plug in horn loaded cone driver?

Posted by [JLH](#) on Mon, 01 Dec 2008 17:32:43 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Norris, There is no reason to use a phase plug in front of a woofer. Its job is to increase high frequency extension, not something you want in a basshorn. Even midbass would be something not worthwhile. Midrange, possibly. Tweeter, definitely. The whole purpose of a phase plug is to make path length the same from all points on the cone/diaphragm to the throat. Without one, sound emanating from the edge travels further than sound coming from the center. The difference causes a phase shift and if enough, cancellation. That's why high frequency suffers without a phase plug. Rgs, JLH

---

---

Subject: Re: Basic requirements for phase plug in horn loaded cone driver?

Posted by [Norris Wilson](#) on Tue, 02 Dec 2008 00:03:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Thanks JLH for your reply. What I gather from your input is that a phase plug is pretty useless for midrange frequencies and below. But, may benefit a wideband driver intended to be used above 3kHz, like a Lowther 6" in the Azura horn. Is there any benefit in using a phase plug for a driver intended to be used from around 150Hz and up to around 2kHz in a horn? Looking at several pro drivers that use a phase plug. I see that they are mostly midrange types like the Beyma 6M180, that have a fairly high frequency extension of 6kHz or more. Are there any specifications for a midrange, or midwoofer that would help identify possible use for horn loading? Thanks Norris

---

---

Subject: Re: Basic requirements for phase plug in horn loaded cone driver?

Posted by [JLH](#) on Tue, 02 Dec 2008 23:49:19 GMT

Norris, You are exactly correct. A phase plug is not required for basshorns but is productive in horns used at high frequency. Rgs, JLH

---

---

Subject: Re: Basic requirements for phase plug in horn loaded cone driver?

Posted by [Wayne Parham](#) on Wed, 03 Dec 2008 02:20:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Another thing to consider is the low-pass acoustic filter formed by the front chamber. In my midhorn, for example, I really don't want output above 2kHz because of cone breakup. The volume of air between the cone and the throat forms a low-pass filter that attenuates high-frequency output, and that's good in this application. To me, you have to consider the cone material and shape when deciding how to horn load it. Just because electro-mechanical parameters are suitable for horn loading doesn't necessarily mean the cone will hold up under compression. The acoustic resistance seems to exacerbate cone breakup modes, so you have to consider that when making a midhorn. I've seen lots of horns like the Oris that have no compression, and they seem to be one of the most popular ways to implement a front loaded fullrange driver. I suspect this is partially due to the breakup modes. Rear loaded horns and transmission lines are also done without compression. On the other hand, there are some midhorns with phase plugs that offer pretty clean output up high. They usually have cones that are purpose designed for horn loading, and a phase plug specifically shaped for the cone and the horn they're mated with. This is a great approach, but not one for the casual DIY'er, I don't think. There's lots of testing involved on the front end, and fabrication and machine work for making the driver, horn and phase plug. So for me, the best approach was to make a cone driven midhorn with front chamber volume appropriate for low-pass. This sets a lower HF limit than a similar horn with a phase plug and cone that allows higher compression. But it has the advantage of being relatively easy to make. The requisite passband is easily obtainable too, when crossing over to a compression horn tweeter.

---

---

Subject: Thanks JLH and Wayne, very enlightning (nt)

Posted by [Norris Wilson](#) on Wed, 03 Dec 2008 06:49:11 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

nt

---

---

Subject: EAW implemented it in their Midbass horn.

Posted by [noviygera](#) on Tue, 18 Aug 2009 06:49:14 GMT

---

The model is MR102L. Do a search.

They claim (and I believe them) that a mid horn that has a 12" driver can be used 200hz to 1.2kHz with the help of a phase plug. Otherwise it would only go up to 900Hz or 1K.

That means it's useful above 900Hz on a 12" driver.

-Herman

---