

---

Subject: speaker positioning

Posted by [jim denton](#) on Mon, 29 Mar 2004 15:52:45 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Ron,,,, Never even entered my mind to try "out" toeing the speakers!!!! I was so focused on moving them for imaging and got so caught up in toeing "in" I never gave them a chance at zero or out toe factors----thanks for the heads up for both the tip and to remember we are suppose to be the guys "out of the box" ---trying the fool stuff that just won't work-----until it does ! Jim

---

---

Subject: Re: speaker positioning

Posted by [jim denton](#) on Mon, 29 Mar 2004 15:54:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Ron----follow up--presently the boxes are set up about 45 inches from the rear wall (measuring to the speaker baffle---and about 26-28 inches from the side wall---this will be interesting to hear---JD

---

---

Subject: Re: speaker positioning

Posted by [roncla](#) on Tue, 30 Mar 2004 12:39:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

YVW.If you look at the FR curve you will see a near flat line at a 30 deg angle off axis.I never run any notch filters in the pipes as it kills the dynamics, but i do run 8 ohm series resistance to up the Qes. The horn is a different matter as with the extreem range and pumped up lower the FR is excellent without anything in the signal path.There is no comparasion between the horn and the pipe the horn gives extreem dynamics with SLAM and an extreem tight FAST bass.Next project is to build a set of horns (the one i built is a prototype out of MDF) and i am going to make a case to enclose the gainclone and P/S into a single cab.ron

---