

---

Subject: Miter cuts with chop saw

Posted by [GarMan](#) on Mon, 10 Jan 2005 02:28:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

In making miter cuts with a chop saw, does it make a difference in the placement of the piece to have the outside face of the frame sit against the fence or away from the fence. For example, the blade on the chop saw is oriented in the 10:30/4:30 position to make a 45 degree cut. Would the good piece be on the right or left of the blade. For some reason, I'm thinking that the 45 degree angle would be sharper on the side that the blade exits verse the side the blade enters. Gar.

---

---

Subject: Re: Miter cuts with chop saw

Posted by [Challanged bySound](#) on Thu, 13 Jan 2005 04:04:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hold the piece of trim work to be cut so it fits against the fence most squarley. work on the side of the wood you fear may chip out more as the entrance. Other than which ever way you like to work it doesnt matter. I like to hold the work with my left hand since holding work on the right side of the blade usually interfears with the motor coming down except on new vertical motor saws. So I often hold the part face out for left side and face in for right side, thus the blade is always angle the same way and I always hld the work on the left of the blade where I can see the blade hit the work easier. Bill

---