Subject: wayne, where do the wires go?
Posted by replay on Wed, 27 Jun 2001 20:04:05 GMT
View Forum Message <> Reply to Message

hi wayne, just received x-overs. thank you very much. the wires with the thingamajigs, where do i attach? thanks. i'll let you know how they sound.

Subject: Crossover installation
Posted by Wayne Parham on Wed, 27 Jun 2001 20:55:02 GMT
View Forum Message <> Reply to Message

1. Connector plate to crossover PCB input with straight wire, (+) to (+) and (-) to (-).2. Woofer to crossover PCB output with straight wire, (+) to (+) and (-) to (-).3. Zobel to woofer, across woofer leads. This is the large block resistor and the capacitor connected in line. Either side goes to woofer (+), the other to woofer (-).4. Tweeter to crossover PCB using tweeter compensation cable assembly. This cable has a block of resistors at one end, and that side connects to the crossover board. The other side connects to the tweeter, (+) to (+) and (-) to (-).I usually mount the crossover PCB and the Zobel resistor on the inside of the cabinet, attaching them to the bottom or back panel with screws. The tweeter cable assembly can either be held in place with a glob of silicon compound or it can rest on a pad of insulation between the PCB and cable assembly. Just be sure it cannot vibrate in contact with something and buzz.

Subject: Re: Crossover installation
Posted by replay on Wed, 27 Jun 2001 23:48:40 GMT
View Forum Message <> Reply to Message

thanks wayne.