
Subject: White Lightning ICs

Posted by [Bill Epstein](#) on Fri, 16 May 2008 02:32:54 GMT

[View Forum Message](#) <> [Reply to Message](#)

I built a pair last week and had problems with the very low heat resistance of the insulation. Trashed a few of the Ken Shindo-approved RCAs. I also wanted to try using all 3 wires, 2 for the neutral. First try I used some shrink tube to overcome the propensity of the thin metal of the shield to come in contact with the hot pin. Jeff Day is right in that his method of crimping and then soldering the folded over neutral wire to the shield is too bulky. I found that using the method for Vampire RCAs, soldering to the shield inside, allowed all 3 to be used. However, the poor heat resistance of the insulation on the hot wire caused a short when it melted from applying heat to the neutral in such close proximity. I used 450 degrees C., less wouldn't get it done. It's essential to tin the wires. You also have to fasten the RCA to the bench (I used tape) as the hot wire wanted to creep out of the barrel when the iron was applied w/o using the crimpers. Soldering the neutral to the crimper(?) before crimping it down solved the problem. Now paying more attention to the heat, and waiting to crimp the hot wire until after heating the joint, the need for shrink tube was eliminated. These RCAs are cheap and the ICs sound about the same as some big name wires I have on loan. They also sound much better than any other DIY attempts I've done with the exception of Cardas Micro-twin terminated with Vampire solid copper \$\$\$ RCAs; maybe even better than the Blue Jeans LC-1. The review has links to the vendors.

White Lightning

Subject: Re: White Lightning ICs

Posted by [colinhester](#) on Fri, 16 May 2008 06:42:54 GMT

[View Forum Message](#) <> [Reply to Message](#)

These sound like a real PitA to construct. Nice photos.....C

Subject: Re: NOT-a-PITA

Posted by [Bill Epstein](#) on Fri, 16 May 2008 11:16:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

Kinda fun, actually, both figuring out what works and seeing the finish.

Subject: Re: White Lightning ICs

Posted by [Shane](#) on Sat, 17 May 2008 17:11:48 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hey Bill, those are slick, and in my budget too !!!! may have to try to make a couple pair.

Subject: Re: White Lightning ICs

Posted by [Bob Brines](#) on Sat, 17 May 2008 22:33:48 GMT

[View Forum Message](#) <> [Reply to Message](#)

And the neat thing is that the Woods extension cords come in white, orange, black and green in 16ga. If you want 14ga, you can get it in yellow. IIRC, the 14ga only comes in orange. If you don't want to fool around with the third wire, you can get 16ga in a variety of colors. It, well, ZIP CORD!! In all seriousness, there are some cables better than 16ga zip cord, but not many. I consider 16ga zip cord to be the standard anything else must beat. Bob

Subject: Re: Upon further review

Posted by [Bill Epstein](#) on Sun, 18 May 2008 00:59:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

One of the most recent pair, which tested perfect, shorted. Sure enough, the thin shield was touching the hot pin. I went back to placing shrink tube over the hot pin and a 1/4" or so of the hot wire. I also revisited the crimp and solder, magnifying the pic Jeff Day took for his review. As you can see, especially if you enlarge with MS My Pictures, one barrel crimp is pressed down and then the neutral is sandwiched between it and the other. This may be a better method of making a good mechanical connection while still protecting the hot wire from the iron heat. I'm kinda obsessing because my previous fave connectors were vampire 800C, \$27/pr and Eichmann at \$44/ set of 4. The Switchcraft have gone up, BTW, ten pieces will now set you back \$18.80.

Subject: Re: Upon further review

Posted by [SteveBrown](#) on Mon, 19 May 2008 20:11:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

How about covering the too-easy-to-melt insulation with a sleeve of teflon, of correct diameter? You solder the shield connection first, right? Then you could even wrap it in teflon tape for a bit better heat and insulation, maybe.
