

---

Subject: SP12

Posted by [mism](#) on Thu, 11 Sep 2003 19:31:33 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Would anyone have experience using a SP12 in a Pi enclosure, if so what tweeter was used?Regardsmism

---

Subject: Re: SP12

Posted by [Wayne Parham](#) on Thu, 11 Sep 2003 21:18:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Sorry, but I'm not familiar with the SP12. Could you post a link or give some information?

---

Subject: Re: SP12

Posted by [mism](#) on Fri, 12 Sep 2003 09:26:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Wayne thanks for your interest, this link is about all that I have for specs,  
[http://www.geocities.com/michael\\_gesualdo/SP12\\_datasheet.html](http://www.geocities.com/michael_gesualdo/SP12_datasheet.html)

[http://www.geocities.com/michael\\_gesualdo/SP12\\_datasheet.html](http://www.geocities.com/michael_gesualdo/SP12_datasheet.html)

---

Subject: Re: SP12

Posted by [Wayne Parham](#) on Fri, 12 Sep 2003 19:44:40 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

We need the electro-mechanical parameters for the drivers to design a good loudspeaker with them. So you'll need to find a way to have them measured.

---

Subject: Re: SP12 speaker data

Posted by [mism](#) on Sat, 13 Sep 2003 10:14:40 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I found this information, perhaps others would appreciate as well. Many pages of speaker data on many speakers. <http://audionova.nu/docs/spkrdata.htm> regardsmism

---

---

Subject: PiAlign'ed Electro-Voice SP12

Posted by [Wayne Parham](#) on Sat, 13 Sep 2003 10:59:32 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I entered the values into PiAlign, using data from the table at your link.  $V_{ad} = V_{as} = 167.1L = 5.9ft^3$   $F_{rd} = F_s = 45Hz$   $Q_d = 1/Q_t = 1/0.67 = 1.5$  PiAlign recommends a 4ft3 cabinet tuned to 25Hz using a 2" diameter port that's 1.5" long. Response is nice, with a gentle 2dB lift from 70hz to 200Hz and -3dB point of 50Hz. Usable response down to 35Hz, at -10dB.

---