
Subject: Pi seven port size using Altec 421A 15" Drivers

Posted by [jumpin](#) on Sun, 09 Nov 2003 17:45:11 GMT

[View Forum Message](#) <> [Reply to Message](#)

I am building a pair of Pi Sevens using altec 421A 15" 8ohm drivers. Could someone advise on correct port length and dia. Any advice on bracing would also be helpful. I am using 18mm MDF. Cheers Jumpin

Subject: Re: Pi seven port size using Altec 421A 15" Drivers

Posted by [Wayne Parham](#) on Sun, 09 Nov 2003 20:41:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

According to "Great Plains Audio," Altec specs for the 421-8H are as follows: $V_{as} = 12.8\text{ft}^3$ $F_{ts} = 32\text{Hz}$ $Q_{ts} = 0.25$ Based on these values, PiAlign recommends a 3.2ft³ cabinet tuned to 48Hz using a port that's 7.5" long, 4.6" tall and 8.2" wide. Response is nice and flat with 60Hz f₃ and 40Hz f₁₀. If this isn't the driver you have, you might consult the Altec T/S Specifications chart at Great Plains Audio to obtain the specs you need.

Subject: Re: Pi seven port size using Altec 421A 15" Drivers

Posted by [Manualblock](#) on Sun, 09 Nov 2003 23:53:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi; What hf driver will you be using if I may ask, Only because I use the 421 in an 4.2cu.ft. enclosure base reflex tiangular shape with an 811/806 on top and the stock 800 hz. xo and would be interested in your choice of hf.

Subject: If I am not mistaken...

Posted by [Shanko](#) on Wed, 12 Nov 2003 00:36:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

..I think Jumpin is using another big round tractrix (Oris variant) loaded with PM2A's. Crossover around 140 hz. He hasn't answered because he is cutting panels for his 7Pi's!
