

---

Subject: 2Pi towers.

Posted by [Peter](#) on Wed, 25 Feb 2004 01:55:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi Wayne. the kit arrived safely. Thank you! When mounting both of the drivers should I use some sort of gasket ie rubber or weatherseal, to ensure air tightness? By the way I've just treated myself to a Jolida tube CD player and a Meixing AC34 tube amp from Hong Kong. I'm very interested to hear how all of this will sound with the 2Pi towers. Also if anyone wants advice on ordering equipment direct from Hong Kong then email me at prbunyan@shaw.ca. Best Peter B.

---

---

Subject: Re: 2Pi towers.

Posted by [Wayne Parham](#) on Wed, 25 Feb 2004 04:56:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

The woofer has a gasket attached. You could certainly put a gasket underneath the tweeter though. I would suggest feeling around the edges while the woofer is played loudly at low frequency and pressurizing the cabinet. If there are any leaks, you will feel them as gusts of air. Usually, when the mounting holes are cut to the right size, the seal is good without any additional gasket material. But if you find something isn't sealed well, you can easily form a gasket with silicon sealant or putty.

---