

---

Subject: 12pi

Posted by [Rajeev](#) on Wed, 12 Oct 2005 07:01:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

This Cab looks to me the next generation of the Lab Sub with all the goodies of the Lab Sub Plus the Tubas ( the added bandpass front chamber ) Wayne You said its push pull , does that mean that one woofer is inverted and connected in reverse polarity so that both radiate in phase . One woofer front loaded and the other rear loaded .

---

---

Subject: Re: 12pi

Posted by [Wayne Parham](#) on Wed, 12 Oct 2005 09:28:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

The push-pull configuration reduces distortion by improving pneumatic symmetry. One driver pressurizes the throat from the front and the other from the rear, both providing pressure in phase with one another. Loudspeaker diaphragm movement isn't perfectly symmetrical because of flux modulation, but the push-pull configuration makes the pressure symmetrical using opposing complementary pairs. When two drivers are used this way, you essentially have a strong one and a weak one on each half-cycle. That way, the overall pressure is equal for both

a lot of information in the threads contained, and I know it's a lot to mull over. But the horn has a lot of design features, and each is given some detail in the threads. In particular, look at the posts

designs". The development history post has several links to previous discussions about each design feature, including a proposed woofer with shorting rings to provide electro-mechanical symmetry, and the reasons why it was not made. That's why the push-pull configuration was chosen instead, because it provides a similar result pneumatically. The evolution of the cooling system is discussed too. In the comparison post, the general performance of basshorns is examined, with studies of various flares, front chambers and rear chambers.

---